

Wood Seating Construction Specifications





TONGUE AND GROOVE CORNER BLOCK SYSTEM



MORTISE & TENON JOINTS (NO DOWELS)

WARRANTEE PERIOD - 2 YEAR FROM DATE OF PURCHASE

Wood

100% European Beech Hardwood - Kiln cured (ALL COMPONENTS MADE IN ITALY)

Construction

Mortise & Tenon glued with custom made glue from Italy specially formulated for beechwood and reinforced with a screw where applicable.

Tongue and groove corner block system reinforced with hanger bolt where applicable. All assembly is performed in-house in our factory.

Stain Colours

CSelect offers standard stain colors as well as custom color matching.

Finishing Process

1. The raw wood frame is thoroughly sanded using 120 grit paper.

2. One coat of water based stain is applied onto the entire chair including the underside of the seat by dipping, not spraying.

3. One coat of water bases sealer is sprayed to completely seal the wood.

- 4. The chair is then sanded again.
- 5. A second application of water based sealer is applied together with a final sanding
- using Scotch Brite pads to remove any sanding marks.
- 6. Finally a water based lacquer is applied ensuring that 100% coverage is obtained.
- This lacquer is very durable and will stand up in a commercial environment, and is 100% eco-friendly.
- 7. A final inspection is performed prior to packaging to ensure a high level of quality control.

Upholstery

1. All upholstery is performed in-house by experienced upholsterers.

2. CSelect uses high density foam. Where necessary, to meet with fire regulations, we use a fire retardant foam together with the necessary barrier (Kevlar) between foam and fabric.

CSelect 195 Clyde Prillaman St Fieldale, VA 24089 276-632-9107

www.cselect.net